

EMLID

REACH RX

Datasheet



Key features

- Tracks GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
- Gets a fix in 5 seconds
- Centimeter precision
- Easy to set up: just add NTRIP
- Comes with the Emlid Flow app
- Pocket-sized and lightweight
- 16 hours on 1 charge
- IP68



REACH RX

Technical specifications

POSITIONING

Precision	RTK	H: 7 mm+1 ppm V: 14 mm+1 ppm
Convergence time		~5 s typically
Signal tracked		GPS/QZSS L1C/A, L2C, GLONASS L1OF, L2OF, BeiDou B1I, B2I, Galileo E1-B/C, E5b
Number of channels		184
Update rates		5 Hz

CONNECTIVITY

Communication interface	Bluetooth 4.2
Ports	USB Type-C
Input data format	RTCM3
Input data protocol	NTRIP
Position output	NMEA

MECHANICAL

Dimensions	172x51x51 mm (6.77x2.00x2.00 in)
Mount	5/8"-11 UNC
Weight	250 g (8.81 oz)
Ingress protection	IP68 (maximum depth of 1.5 meters up to 30 minutes)
Operating t°	-20 to + 65 °C

ELECTRICAL

Autonomy	Up to 16 hrs
Battery	Li-Ion 5200 mAh, 3.6V, 18.72 Wh
Charging	USB Type-C, 5V, 2A
Certification	FCC, CE, IC

EMLID SOFTWARE AND SERVICES

Emlid Studio

Easy-to-use free software to simplify your post-processing workflow.



Emlid Flow

Android & iOS survey app for data management.



Emlid NTRIP Caster

Stream corrections to your RTK GNSS receivers over the Internet.



YOUR LOCAL DEALER



Contact Details

12500 Castlebridge Drive
Houston, TX 77065

282-890-8290
888-2RENT3D (273-6833)

<https://hts-3d.com>